

125/250/500/1000 Hz, 94/104/114 dB

MULTI FREQUENCY/LEVEL SOUND LEVEL CALIBRATOR

Model : SC-934

ISO-9001, CE, IEC1010

www.yalab.com.tw

02-2389-0101



Lutron

www.YaLAB.com.tw

The Art of Measurement

125/250/500/1000 Hz, 94/104/114 dB

MULTI FREQUENCY/LEVEL SOUND LEVEL CALIBRATOR

Model : SC-934

www.YaLAB.com.tw 02-2389-0101

FEATURE

- * Multi Frequency
- * Multi level output
- * Standard 94 dB/1 KHz
- * Sound calibrator, useful to calibrate another "
- * Sound Level Meter " precisely.

SPECIFICATION(23±5 °C)

Frequency	125/250/500/1 KHz (Red LED indicator) ±2%
Sound Pressure Level for SPL	94/104/114 dB (Red LED indicator) ±0.5 dB. <i>* Spec. tested under the environment RF Field Strength less than 3 V/M & frequency less than the 30 MHz only.</i>
Suitable Microphone Type	1 " mic. & 0.5 " mic. <i>* 0.5" microphone is calibrated with 0.5" mic. adapter(standard acc.)</i>
Distortion	94 dB range harmonic distortion : ± 2 %.
Operating Temp.	0 °C to 50 °C (32 °F to 122 °F).
Operating Humidity	Less than 80% R.H.
Operating Atmospheric Pressure	65kPa ~ 108kPa
Power Supply	DC 9 V battery (006P, 6F22) x 1 PC. <i>* Recommend use the Alkaline or Heavy duty type battery.</i>
Power Consump.	Approx. DC 8 mA (in ON position)
Low Battery indicator	Build in " Low Battery Indicator " LED
Dimension	124 mm x 63 mm x 40 mm.
Weight	Approx. 277 g/0.61 LB (meter only).
Accessories Included	Instruction manual. 1 PC. 0.5" mic. adapter. 1 PC. Carrying case, CA-03 1 PC.

* Appearance and specifications listed in this brochure are subject to change without notice.

SC-934+190808

www.YaLAB.com.tw 02-2389-0101